

Scott Wilson Mining



COMMANDER RESOURCES LTD.

**TECHNICAL REPORT ON THE
STORM COPPER PROJECT,
SOMERSET ISLAND, NUNAVUT,
CANADA**

NI 43-101 Report

Authors:

R. Barry Cook, M.Sc., P.Eng.

Christopher Moreton, Ph.D., P.Geo.

February 15, 2009

SCOTT WILSON ROSCOE POSTLE ASSOCIATES INC.

TABLE OF CONTENTS

	PAGE
1 SUMMARY	1-1
Executive Summary	1-1
Technical Summary	1-8
2 INTRODUCTION AND TERMS OF REFERENCE	2-1
3 RELIANCE ON OTHER EXPERTS	3-1
4 PROPERTY DESCRIPTION AND LOCATION	4-1
5 ACCESSIBILITY, CLIMATE, LOCAL RESOURCES, INFRASTRUCTURE AND PHYSIOGRAPHY	5-1
6 HISTORY	6-1
7 GEOLOGICAL SETTING	7-1
Regional Geology	7-1
Property Geology	7-9
8 DEPOSIT TYPES	8-1
9 MINERALIZATION	9-1
Seal Zinc	9-1
Storm Copper	9-2
10 EXPLORATION	10-1
11 DRILLING	11-1
12 SAMPLING METHOD AND APPROACH	12-1
13 SAMPLE PREPARATION, ANALYSES AND SECURITY	13-1
14 DATA VERIFICATION	14-1
15 ADJACENT PROPERTIES	15-1
16 MINERAL PROCESSING AND METALLURGICAL TESTING	16-1
17 MINERAL RESOURCE AND MINERAL RESERVE ESTIMATES	17-1
18 OTHER RELEVANT DATA AND INFORMATION	18-1
19 INTERPRETATION AND CONCLUSIONS	19-1
20 RECOMMENDATIONS	20-1
21 REFERENCES	21-1
22 SIGNATURE PAGE	22-1
23 CERTIFICATE OF QUALIFICATIONS	23-1
24 APPENDIX 1	24-1

SGS Analytical Procedures	24-1
Global Discovery Labs Analytical Procedures	24-3

LIST OF TABLES

	PAGE
Table 1-1 Proposed Budget – Storm Copper Project	1-7
Table 4-1 Prospecting Permit Details	4-1
Table 5-1 Weather Statistics, 1961-1990; Resolute, Nunavut, Canada	5-2
Table 9-1 Selected Drill Hole Results from the 2200N Zone	9-5
Table 9-2 Selected Drill Hole Results from the 2750N Zone	9-7
Table 9-3 Selected Drill Hole Results from the 3500N Zone	9-8
Table 9-4 Selected Drill Hole Results from the 4100N Zone	9-11
Table 11-1 Historical Drilling	11-1
Table 14-1 Independent Assays of Drill Core	14-1
Table 20-1 Proposed Budget – Storm Copper Project	20-2

LIST OF FIGURES

	PAGE
Figure 4-1 Location Map	4-3
Figure 4-2 Property Map	4-4
Figure 7-1 Regional Geology	7-5
Figure 7-2 Local Geology	7-6
Figure 7-3 Stratigraphic Column, Northwest Somerset Island	7-8
Figure 7-4 Storm Property Geology	7-17
Figure 7-5 Stratigraphic Column – Lower Cape Storm Formation and Upper Allen Bay Formation	7-18
Figure 9-1 Interpreted Geological Solids for Storm 4100N	9-13
Figure 9-2 4100N Zone Drill Plan with Copper Assay Composites	9-14

1 SUMMARY

EXECUTIVE SUMMARY

INTRODUCTION

Scott Wilson Roscoe Postle Associates Inc. (Scott Wilson RPA) was retained by Mr. Ken Leigh, President and CEO of Commander Resources Ltd. (Commander), to prepare an independent Technical Report on the Storm Copper Project, on Somerset Island, Nunavut. The purpose of this report is to qualify the historical work and data, to estimate a mineral resource based on historical drilling on the 4100N Zone, and to provide recommendations for the next work program. This Technical Report conforms to NI 43-101 Standards of Disclosure for Mineral Projects. Scott Wilson RPA visited the property on July 25, 2008.

INTERPRETATION AND CONCLUSIONS

Historic exploration work on and around the three Prospecting Permits comprising the Storm Copper property has defined two areas with radically different types of mineralization. Each of these mineralization styles occurs at its own specific stratigraphic interval: the stratabound Seal Zinc deposit occurs in the Lower to Middle Ordovician Ship Point Formation, while the stratigraphic and/or structurally controlled Storm Copper Zones occur at least 800 m higher at the top of the Upper Ordovician to Upper Silurian Allen Bay Formation.

SEAL ZINC

The Seal Zinc deposit is hosted primarily by a 15 m thick quartz arenite unit that contains interbeds of dolostone and sandy dolostone. The host arenite occurs two metres above the base of the Ordovician Ship Point Formation which conformably overlies the Turner Cliffs Formation. Information from diamond drilling suggests that the overall geometry of the mineralized zone is lensoid in nature but definitely stratabound. The best zinc mineralization is coarse-grained, banded, red-brown, blackjack and yellow colloform sphalerite. These varieties occur within, or as total replacements of, the sandy dolostone interbeds, although they also occur as interstitial disseminations in the massive sandstone beds. Fine-grained marcasite is the dominant iron sulphide, with lesser coarse-grained

pyrite occurring where the dolostone interbeds are more common. Good silver values are associated with the sphalerite. Empirically, the Seal Zinc mineralized zone is classified as a carbonate replacement deposit (CRD).

Within the Turner Cliffs Formation, in the immediate stratigraphic footwall of the mineralized zone, there is an extensive zone of alteration that is traceable for at least 500 m along strike and down to a depth of at least 120 m. The width of this alteration zone is unknown. It consists of pervasive solution breccias and pseudobreccia textures cemented by coarse white dolospar; this alteration is typical of carbonate replacement zinc-lead sulphide deposits. Within this alteration zone, there is some sulphide mineralization, typically coarse red-brown and blackjack sphalerite associated with the dolospar cement and locally disseminated in the dolostone matrix. Low zinc values were intersected by drilling within the alteration zone. This alteration and mineralization is believed to represent the plumbing or feeder system to the accumulated sulphides of the Seal Zinc Zone.

As defined by drilling, the Seal Zinc deposit is approximately 400 m long, 50 m to 100 m wide and 12 m to 20 m thick. The average grade of the deposit is 7% Zn to 8% Zn and 23 g/t Ag to 27g/t Ag. Metric intervals within the zone contain up to 33% Zn and 140 g/t Ag. A historic “geological resource” of 2 Mt grading 8% Zn and 30 g/t Ag was estimated from the drilling by Cominco Ltd. (Cominco) geologists in 1997. Scott Wilson RPA cautions that there are no data available to independently verify the historical resource. Consequently, it should not be relied upon. The limits of the Seal Zinc deposit appear to have been defined, but there is potential for this type of mineralization to occur elsewhere on the property.

STORM COPPER

The stratigraphically and/or structurally controlled copper mineralization offers the most interesting economic potential on the Storm Copper property. The style of mineralization is a variant on what could be called generically a sediment-hosted copper deposit. The mineralization is epigenetic, carbonate hosted and located within an intracratonic sedimentary basin that was modified by folding and faulting. Local ground